



US008070090B2

(12) **United States Patent**
Tayman

(10) **Patent No.:** **US 8,070,090 B2**
(45) **Date of Patent:** **Dec. 6, 2011**

(54) **STOP-ROTOR ROTARY WING AIRCRAFT**

(75) Inventor: **Steven K. Tayman**, Alexandria, VA (US)

(73) Assignee: **The United States of America as represented by the Secretary of the Navy**, Washington, DC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 420 days.

(21) Appl. No.: **12/486,023**

(22) Filed: **Jun. 17, 2009**

(65) **Prior Publication Data**

US 2010/0230547 A1 Sep. 16, 2010

Related U.S. Application Data

(60) Provisional application No. 61/094,794, filed on Sep. 5, 2008.

(51) **Int. Cl.**
B64C 27/22 (2006.01)

(52) **U.S. Cl.** **244/7 C; 244/6**

(58) **Field of Classification Search** **244/6, 7 A, 244/7 B, 7 C, 7 R, 12.4, 17.11, 17.19, 17.21, 244/45 R, 48**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,423,625 A	7/1947	Smith
2,483,480 A	10/1949	Stalker
3,035,789 A	5/1962	Young
3,179,352 A	4/1965	Nelson
3,506,219 A	4/1970	Mouille et al.
3,884,431 A	5/1975	Burrell

4,093,155 A	6/1978	Kincaid, Jr.
4,923,144 A	5/1990	Eickmann
4,925,131 A	5/1990	Eickmann
D311,719 S	10/1990	Haga
5,381,985 A	1/1995	Wechsler et al.
5,799,900 A *	9/1998	McDonnell 244/7 A
5,839,691 A	11/1998	Lariviere
6,082,671 A	7/2000	Michelson
6,206,324 B1	3/2001	Smith
6,227,481 B1	5/2001	Fenny et al.
6,367,736 B1	4/2002	Pancotti
6,607,161 B1	8/2003	Krysinski et al.
6,626,398 B1	9/2003	Cox et al.
6,655,631 B2	12/2003	Austen-Brown
6,659,394 B1	12/2003	Shenk
6,695,254 B2	2/2004	Zoppitelli et al.

(Continued)

OTHER PUBLICATIONS

Tayman, S.K., Walden, A.B., "An Investigation of the Aerodynamic Performance of the Spin-Wing Concept", NRL/MR/5710—98-8147, pp. 1-17, Feb. 27, 1998.

(Continued)

Primary Examiner — Joshua Michener

Assistant Examiner — Nicholas McFall

(74) *Attorney, Agent, or Firm* — Amy L. Ressing; Sally A. Ferrett

(57) **ABSTRACT**

Systems and methods for transitioning an aircraft between helicopter and fixed wing flight modes are provided. In one embodiment, an aircraft comprises a plurality of wings each having a spar and a flap; a flap actuator configured to move the flap with respect to the spar; and a center section rotatably coupled to each spar. The center section includes at least one spar actuator configured to rotate at least one of the wings about a rotational axis of the spar when the aircraft transitions between helicopter and fixed wing flight modes.

9 Claims, 7 Drawing Sheets

